1.1 An Investigation of the Influence of Urban Areas on Rainfall Using a Cloud-Mesoscale Model and TRMM Satellite

J. Marshall Shepherd NASA Goddard Space Flight Center Greenbelt, MD 20771

1.0 Introduction

The urban heat island (UHI) has become a widely acknowledge, observed, and researched phenomena because of its broad implications. It is estimated that by the year 2025, 80% of the world's population will live in cities (UNFP, 1999). The UHI has been documented in the literature to affect local and regional temperature distributions, wind patterns and air quality. The UHI can also impact the development of clouds and precipitation in and around cities. This paper will focus primarily on the UHI's impact on precipitation.

In the past 30 years, several observational and climatological studies have theorized that the UHI can have a significant influence on mesoscale circulations and resulting precipitation (see Shepherd et al. 2002 for a thorough review). More recent studies have continued to validate and extend the findings from preand post-METROMEX investigations. Shepherd et al. (2002) was one of the first (and possibly the first) attempts to identify rainfall modification by urban areas using satellite-based rainfall measurements. Using a 15-month (spanning three years) analysis of mean rainfall rates, the cities of Atlanta, Montgomery, Dallas, Waco, and San Antonio were examined. Shepherd et al. (2002) found that the average percentage increase in mean rainfall rate in a hypothesized "downwind maximum impact area" over an "upwind control area" was 28.4% with a range of 14.6 to 51%. The typical distance of the downwind rainfall rate anomaly from the urban center was 30-60 km, consistent with earlier studies. This fact provides confidence that UHI-rainfall effects are real and detectable by TRMM satellite estimates.

A recent U.S. Weather Research Program panel concluded that more observational and modeling research is needed in the area of urban-induced rainfall anomalies (Dabberdt et al 2000). In terms of modeling research, several studies have addressed the evolution and impact of the UHI on the environment, but very few have focused on the impact to precipitation processes. Kidder (1999) provide a fairly thorough review of UHI modeling studies that do not specifically address the precipitation modification. Investigators have begun to explicitly address the impact of urban surfaces on rainfall processes (Thielen et al. 2000; Baik et al. 2001).

Herein, a convective-mesoscale model with extensive land-surface processes is employed to (a) determine if an urban heat island (UHI) thermal perturbation can induce a dynamic response to affect rainfall processes and (b) quantify the impact of the following three factors on the evolution of rainfall: (1) urban surface roughness, (2) magnitude of the UHI temperature anomaly, and (3) physical size of the UHI temperature anomaly. The experiments are achieved by inserting a slab of land with urban properties (e.g. roughness length, albedo, thermal character) within a rural surface environment and varying the appropriate lower boundary condition parameters.

2.0 Early Results

We employ a set of sensitivity experiments in twodimensions (x-z grid at 0.5 km resolution). The Advanced Regional Prediction System (ARPS) model is applied using a "sand-box or urban slab" approach. A 30-km urban area is defined in the initial land surface parameters. In the simulations, the desert land type with sand is chosen to simulate the thermal properties closest to an urban surface. The prevailing flow is westerly and based on a summer 1996 Atlanta sounding day studied by Bornstein and Lin (2000). In the CONTROL experiment, the initial horizontal temperature anomaly profile varies linearly from 0.0° at the urban edges to 2.0° at the urban center. The roughness length increases linearly from 0.01 (edges) to 1.0 m (urban center). The vegetation fraction also decreases linearly from 0.3 (edges) to 0.1 (urban center). Each of these initial model profiles is based on the classical, idealized UHI distribution of temperature, roughness, and vegetation in an urban area.

Very preliminary results from the study suggest that roughness exerts a control on the amount and timing of urban-induced precipitation falls directly over In an experiment with no variation (NOROUGH-West) in roughness across the urban area (e.g. constant roughness length of 0.01 m), rainfall was generated 20-30 km downwind of the urban center (Fig. 1) However, when the variation in temperature (NOUHI) was removed (e.g. constant 2° horizontal profile), the precipitation is found over the city. In NOUHI, the variation in roughness is the primary forcing and results indicate enhanced low-level convergence prior to convective development over the In experiments (not shown) INCREASED (REDUCED) the roughness at the center is increased to 2.0 m (decreased to 0.5 m). In each of these experiments the distribution and magnitude of the rainrates did not significantly differ from the CONTROL. These preliminary results, consistent with other studies, suggest that roughness length promotes increased forcing through focusing low-level convergence, primarily over the city. Results also show a tendency for experiments with increased roughness length to initiate convection 10-25 minutes earlier than the CONTROL experiment.

In NOROUGH-West, roughness was not a factor so that only the UHI thermal perturbation was generating the forcing that ultimately led to precipitation. Examining fig. 1, it is apparent that the primary precipitation region is downwind in NOROUGH-West. After examining perturbation vertical velocity fields from the model run, it is theorized that small mesoscale circulations form at the edges and center of the urban area due to gradients in the surface flux. In NOROUGH-West, the prevailing flow at all levels is westerly. Under westerly flow, an enhanced convergence zone is created between the prevailing wind flow at low- to mid-levels and the eastern-most mesoscale circulation (see fig. 2). In NOROUGH-EAST, the roughness variation is removed and the prevailing flow is reversed to easterly. As theorized, the precipitation regime shifted to the downwind region west of the "city".

A set of experiments (not shown due to space restrictions) has also been conducted in which the size




Figure 1-Rainfall Rates as a function of time.

of the urban area varies from 20 km to 40 km using the same initial profiles as the CONTROL experiment. Early results suggests that smaller cities tend to produce a maximum in rainfall downwind of the city while larger cities produce a maximum in rainfall over and slightly downwind of the center of the city. This finding is consistent with some of Thielen et al. 's (2001) work. Another set of experiments varies the initial magnitude of the surface perturbation from 2.0 ° to 8.0°. In these experiments, the distribution and location of precipitation does not vary significantly, but a downwind region of precipitation is significantly greater for the 8° UHI than the smaller magnitude UHI. This outcome is likely due to larger boundary layer destabilization resulting in more vigorous mesocirculations (Fig. 2).

3.0 Concluding Remarks

The paper introduces *very* preliminary results from the modeling component of a remote sensing-modeling effort on urban induced rainfall. Such research has implications for weather forecasting, urban planning, water resource management, and understanding human impact on the environment and climate.




Figure 2-Preferred UHI convergence regions.

GSFC STI PUBLIC DISCLOSURE EXPORT CONTROL CHECKLIST

The Export Control Office requests your assistance in assuring that your proposed disclosure of NASA scientific and technical information (STI) complies with the Export Administration Regulations (EAR, 15 °CFR 730-774) and the International Traffic In Arms Regulations (ITAR, 22 °CFR 120-130). The NASA Export Control Program requires that every domestic and international presentation/publication of GSFC STI be reviewed through the GSFC Export Control Office in accordance with the NASA Form 1676 NASA Scientific and Technical Document Availability Authorization (DAA) process. Release of NASA information into a public forum may provide countries with interests adverse to the United States with access to NASA technology. Failure to comply with the ITAR regulations and/or the Commerce Department regulations may subject you to fines of up to \$1 million and/or up to ten years imprisonment per violation. Completion of this checklist should minimize delays in approving most requests for presentation/publication of NASA STI.

Generally, the export of information pertaining to the design, development, production, manufacture, assembly, operation, repair, testing, maintenance or modification of defense articles, *i.e.*, space flight hardware, ground tracking systems, launch vehicles to include sounding rockets and meteorological rockets, radiation hardened hardware and associated hardware and engineering units for these items are controlled by the State Department under the ITAR. A complete listing of items covered by the ITAR can be accessed at http://gsfc-bluenun.gsfc.nasa.gov/export/regsitar.htm. The export of information with respect to ground based sensors, detectors, high-speed computers, and national security and missile technology items are controlled by the U.S. Commerce Department under the EAR. If the information intended for release falls within the above categories but otherwise fits into one or more of the following exemptions, the information may be released.

missile technology items are cabove categories but otherwis	controlled by the U.S. Commerce De e fits into one or more of the following	partment under the EAR. If the information intended for release falls within the age exemptions, the information may be released.					
by the Export Control Office,	KEMPTION I your information is already in the public domain in it's entirety through a non-NASA medium and/or through NASA release previously approved the Export Control Office, the information is exempt from further review. If the information falls into this category, you may attest that you are ing this exemption by signing below.						
Signature	Date						
without the disclosure of info launch vehicles, the informat exemption by sighing below. Signature EXEMPTION III If your information falls into	the areas of concern as referenced at	data, <i>i.e.</i> data pertaining to studies of clouds, soil, vegetation, oceans, and planets, led by the ITAR or EAR, such as flight instruments, high speed computers, or the information falls into this category, you may attest that you are using this love, but is offered at a general purpose or high level, <i>i.e.</i> poster briefs and AR controlled items is offered, the information is exempt from further review. If e using this exemption by signing below.					
Signature	, Date						
EXEMPTION IV							
	orded only to agencies of the Federal	ove, the information may be released using exemption 125.4(b)(13) of the ITAR. Government and allows the release of ITAR controlled information into the public at use of this exemption will be allowed only after we receive assurance that such the use of this exemption. That the information					

cited by the author. If you determine that you have met this criteria, you may attest your determination by signing below, and the GSFC Export Control Office will offer favorable consideration toward approving your presentation/publication request under this special exemption.

Signature Date

If you do not satisfy the above exemptions, please contact the GSFC Export Control Office for further clarification on the releasability of your information under the ITAR or EAR.

release is a responsible action. To this end, an internal guideline has been established pursuant to the use of this exemption: That the information does not offer specific insight into design, design methodology, or design processes of an identified ITAR controlled item in sufficient detail (by itself or in conjunction with other publications) to allow a potential adversary to replicate, exploit and/or defeat controlled U.S. technologies. All signatures of approval on NASA Form 1676 expressly indicate concurrence with the responsible use of Exemption IV when Exemption IV has been